

T2365 MC



Tally

Highlights at a glance:

- Up to 9 part forms
- Full range of automatic features to minimize user intervention
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- **Optional Interfaces:** RS232 Serial; Coax/Twinax; Ethernet IPDS

The T2365 MC printers are rugged and powerful high speed matrix printers for heavy duty operation under the most extreme conditions. Reliable, heavy workload output is guaranteed for many years following printer purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the ,straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Configurations:

• T2365 MC G

Standard Product with IGP/PJL Support





T2365 MC

Print Speed	900 cps (Fastest Draft); 640 cps (Draft), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	605 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/100BaseT
Optional Connectivity	Serial RS232, Ethernet Multiprotocol, Ethernet with SCS or IPDS support,
	Coax with SCS or IPDS support, Twinax with SCS or IPDS support
Standard Emulation	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP
	IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Optional Emulation	PCL 3 (Rugged Writer)
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes
	and large character printing
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path,
	tear off and park position
Optional Paper Handling	Additional push tractor (front),
	Automatic cutting device
Number of Copies	Push tractor front: 1 original + 8 copies;
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 420 mm; Length: 76 to 559 mm
Physical Weight	19 kg
Physical Size	624 x 432 x 280 mm (W x D x H)
Acoustic	59 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	60 Watt Printing; 18 W Power Save
Temperature	+10° to +35° C; 20% to 80% humidity
Workload	48.000 pages per month
MTBF	22.500 hours
Drivers	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP

DASCOM GB Limited

Hart House, Priestley Road Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 355130 — Fax: +44 1256 481400

in fo.gb@dascom.com-www.dascom.com

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS