

## T2250



*Tally*

The T2250 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

### Highlights at a glance:

- Print speeds **up to 720 cps**
- **26,000 pages per month** workload
- 136 columns
- 24 pin print head produces excellent print quality
- **Automatic gap adjustment** and quick tear
- **Straight through paper path** for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 53 dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

### Configurations:

- **T2250** Standard Product
- **T2250 IGP** with IGP/PJL Support

## T2250

<b>Print Speed</b>	720 cps (Fastest Draft); 600 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	482 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	400 million characters
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and serial RS232
<b>Optional Connectivity</b>	Serial Current Loop (20mA), Ethernet 10/100BaseT
<b>Standard Emulation</b>	IBM ProPrinter XL24, Epson LQ2250, MTPL + Barcode + LCP <b>IGP Version:</b> IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Optional Emulation</b>	DEC LA 75, ECMA 9011, MT50
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and large character printing
<b>Consumables</b>	Ribbon: 5 million characters
<b>Standard Paper Handling</b>	Push tractor and friction (front), continuous paper with straight paper path, cut sheet front insertion, tear off and park position
<b>Optional Paper Handling</b>	Additional push tractor (front), additional push tractor (rear), Automatic sheet feeder rear (100 sheets) or front (50 sheets),
<b>Number of Copies</b>	Push tractor front: 1 original + 5 copies; Push tractor rear: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 to 420 mm; Length: 76 to 599 mm
<b>Physical Weight</b>	13,2 kg
<b>Physical Size</b>	600 x 300 x 295 mm (W x D x H)
<b>Acoustic</b>	53 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	40 Watt Printing; <10 W Sleep Mode
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity
<b>Workload</b>	26.000 pages per month
<b>MTBF</b>	10.000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7 and Server 2003/2008; SAP

### DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 481481 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 