

DP-581

Large print
with small dimensions



HIGHLIGHTS AT A GLANCE:

- Easy-to-read control interface and simple drop-in paper loading.
- Dual tear bars allow easy tear-offs
- True WYSIWYG printing with the Windows driver.
- Printer integration is quick and easy with Windows driver or Android™ and Microsoft SDKs



DP-581

The DP-581 is a low profile, highly reliable mobile printer for a variety of applications. Fully self-contained unit means easy to deploy and easy to use.

This printer is great for when workers need to stay focused on their job, not their printers. That's because the DP-581 is engineered to create crisp, professional looking full page receipts, tickets, invoices, schematics, etc. automatically and reliably. One look will convince you — DP-581 takes full page mobility and ease of use to a whole new level.

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|--|
| Print speed | Up to 2 inch/sec (50 mm/sec) |
| Resolution | 203 dp (8 dots/mm) |
| Lifetime print head | 50 km |
| Memory | 256 kB FLASH, 512 MB DRAM |
| Print width | Up to 216 mm |
| Interfaces Standard | USB 2.0 (Typ C) |
| Interfaces Optional | Bluetooth (4.0) or WiFi (802.11 b/g/n) |
| Bluetooth | Compatible Bluetooth 4.0 Stack Protocols: L2CAP, RFCOMM, SDP Profile: GAP, SDAP, SPP, BTLE |
| WiFi | Encryption: WEP, WPA-PSK/TKIP, WPA2-AES, 802.1x EAP with TLS, TTLS, LEAP, FAST, PEAP |
| Administration | Internal Website |
| Emulations | Zebra CPCS and ZPL, EPL, ESC/POS, PostScript, Exttech, IPL |
| Roll diameter | Max. diameter 50,8 mm |
| Roll capacity | Approx. 30 m (equals 100 DIN A pages) |
| Battery | Rechargeable 6 cells Lithium-Ion (5.900 mAh) Endurance more than 300 printed pages Charging time 5,7 hours |
| Weight | 1,6 kg (standard model); 1,95 kg (battery model) |
| Dimensions | 305 x 64 x 107 mm (W x D x H) |
| Voltage | 19 V; 3,4 A |
| Power consumption | 30 Watt (printing); 1,9 Watt (stand-by) |
| Temperature | -18° to +50° C (printing); -20° bis 60° C (storage) |
| Humidity | 10% to 90% rel. humidity |
| MTBF | 10.000 hours |
| Drivers | Windows 7/8/10, Windows CE/Pocket PC, Windows Mobile, Android |
| Certifications | CE, FCC Class B, UL, E1 |

Configurations:

- **DP-581** Standard model
- **DP-581** Battery model

DASCOM GB Ltd
Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047